

4

3

2

1

INDUSTRIAL PUMP

STAINLESS STEEL  
FLOAT TANK

APPLICABLE MACHINES		
MODEL	APPROX. WEIGHT	
	LB	KG
EN3.0S250-60XP	1500	682
EN2.4S250-50XP		

NOTE: CASTERS ADD 8" (20.32cm) TO HEIGHT  
SKID WILL ADD 6" (15.24cm) TO HEIGHT

EXPLOSION PROOF ENCLOSURE:  
UL/cUL CERTIFIED FOR USE IN  
CLASS I DIV. 1 GROUP C & D  
CLASS II DIV. 1 GROUP F&G

NOTE:  
MAINTENANCE REQUIRES 4' MIN. ON ELEMENT  
HEAD SIDE AND 2' MIN. ON ALL OTHER SIDES

MOTOR:  
CLASS I DIV. 1 GROUP C, D  
CLASS II DIV. 1 GROUP F, G

POWER INLET  
LOCATION  
(2" NPT)

WATER INLET  
(3/4" GARDNER HOSE CONNECTION)

HEATING ELEMENTS

[109.22cm]  
43"

[100.33cm]  
39 1/2"

WATER OUTLET  
(3/8" NPT)

[143.51cm]  
56 1/2"

Copyright © 2010 SIOUX CORPORATION. This information is property of Sioux Corporation, is subject to recall at any time, and is not to be used in any way detrimental to Sioux's interest. Use of material is subject to the Terms of Website Use listed on the www.siuox.com website.

**PROPRIETARY AND CONFIDENTIAL**  
THE INFORMATION CONTAINED  
IN THIS DRAWING IS THE SOLE  
PROPERTY OF SIOUX CORP.  
ANY REPRODUCTION IN PART OR  
AS A WHOLE WITHOUT WRITTEN  
PERMISSION OF SIOUX CORP  
IS PROHIBITED.

UNLESS NOTED:  
DIMENSIONS  
**INCHES**  
TOLERANCES  
LINEAR: ±.0625  
[1/16]  
ANGULAR: ±2°

DRN LC 07-16-14  
CHK  
SIZE A SCALE 1:20  
THIRD-ANGLE PROJECTION

<b>SIOUX</b> SIOUX CORPORATION, ONE SIOUX PLAZA, BERESFORD, SD 57004		EN-SERIES THREE ELEMENT P-SERIES XP MACHINES	
		FR21124-W P-SERIES	REV A-05 SH 1/1

DO NOT SCALE DRAWING

4

3

2

1

FR21124-W P-SERIES A-05 1/1